

NotchTrack™ NT

WALL SUPPORT

Wall Backing & Bridging Alternative

NotchTrack™ NT Used for Wall Bridging^{1,2}



NotchTrack™ Series	Allowable Axial Load (Lbs)					
	16" o.c. Stud Spacing			24" o.c. Stud Spacing		
	4"	6"	8"	4"	6"	8"
NT43 (50 ksi)	977	1512	2047	977	1512	2047
NT68 (50 ksi)	3541	5460	7380	3541	5460	7380

NotchTrack™ Series	Allowable Hanger Load (Lbs)					
	16" o.c. Stud Spacing			24" o.c. Stud Spacing		
	4"	6"	8"	4"	6"	8"
NT43 (50 ksi)	1992	1377	1030	1288	1377	1030
NT68 (50 ksi)	3665	5350	4087	2371	4135	4087

- Table data based on 1.25" track leg, but other leg sizes are available

NotchTrack Depths: 4", 6", and 8"

Leg Size: 1.25"

Available Thicknesses: 43, and 68 Mils

Nomenclature

NotchTrack is manufactured in 10 ft. lengths. NotchTrack is designated by track depth in inches multiplied by 100, followed by type (NT), leg size, mil thickness and notch spacing.

Example: 400 NT 125 - 43 - 16oc
(Inside Track Dimension) (NotchTrack) (Leg) (Thickness) (Notch Spacing)

****SPECIAL LENGTHS AVAILABLE UPON REQUEST****

NotchTrack™ NT Used for Wall Backing



¹ Use NotchTrack in conjunction with flat strap and blocking where applicable.

² Design screw connection of track to stud for actual design load



MEETS OSHA & IBC
LOAD REQUIREMENTS

ALL MATERIAL 50 KSI STEEL



1.888.474.4876
www.steelnetwork.com

CALL TSN TODAY: 1-888-474-4876

NotchTrack NT is available through your local dealer
Quality Light Steel Framing Connections and Members